

- Pedestrian Areas**
- Walkways**
- Building Entrances**
- Parking Lots**
- Shopping Malls**
- Landscape Areas**



AA-35/AA-36



AA-135/AA-136

Specifications



Certifications ETL and CETL listed for wet location. Meets IP65 standard.

Housing The housing shall be constructed of heavy duty cast aluminum with a minimum 3/16" wall thickness.

Shade The shade shall be constructed of heavy duty cast aluminum with a minimum 3/16" wall thickness.

Mounting Detail The fixture arm shall internally slip fit a 3" or 4" O.D. pole. Consult Factory for other pole sizes.

The Arm Mount (AM) brackets shall externally slip fit a 3" or 4" O.D. pole. Consult Factory for other pole sizes.

The pendant mounted option (P) is supported by an aluminum pipe 1" O.D. (specify length) with a hang straight bracket (max. 25° slope) attached with two 3/8" bolts on a 5-3/4" bolt circle and a canopy for mounting over a recessed 4" square junction box.

Ballast The ballast shall be readily accessible, removable and insulated. The fixture is to be pre-wired and electronically tested before shipment.


Lens The lens shall be opal acrylic for wide angle light distribution.

Lamp Holder The standard lamp holder shall be 4KV pulse rated medium base, for HID and Incandescent lamp sources.

Hardware All exposed hardware shall be stainless steel.

Finish BK-BZ-WH-GR-GY-NA are thermoset polyester powder coat. Custom color available upon request.

PROJECT
FIXTURE TYPE
CATALOG#

 Some luminaires use fluorescent or high intensity discharge (HID) lamps that contain small amounts of mercury. Such lamps are labeled "Contains Mercury" and/or with the symbol "Hg." Lamps that contain mercury must be disposed of in accordance with local requirements. Information regarding lamp recycling and disposal can be found at www.lamprecycle.org

AA-135/AA-136

AA-35/AA-36

Product Order Guide

Series	Max Watts	Lamp Type	Voltage ¹	Finish ²	Options
AA-35	13CF	CF	120	BK Black	WM Wall Mount
AA-135	26CFQ	CFQ	208	BZ Bronze	P ³ Specify Pendant Length
	42CFT	CFT	240	WH White	
	70MH	T6	277	GR Green	AM2180 ⁴ Pole adaptor 2 @ 180°
	70HPS	E17		NA Natural Aluminum	AM3120 ⁴ Pole adaptor 3 @ 120°
	100MH	E17		GY Gray	AM490 ⁴ Pole adaptor 4 @ 90°
				CC Custom Color	
AA-36	150HPS	E17			
AA-136	150MH	T6			
	150MH	E17			

¹ Consult factory for other voltages.

² Thermoset polyester powder coat standard. Custom colors available on request.

³ Specify pendant length in inches or mm.

⁴ Specify pole size.

Note: E17 Lamps 150W and below are medium base
CF=single biax, CFQ=double biax, CFT=triple biax

Example: AA-35-100MH-E17-277-BK-WM

Luminaire Dimensions

Luminaire	A		B		C		D		EPA	Weight	
	Inch	mm	Inch	mm	Inch	mm	Inch	mm		lbs.	kg
AA-35	35.00	889	17.50	445	21.00	533	10.00	254	0.81	22	10.0
AA-35-WM	11.00	279	7.00	178	35.75	908			1.14	28	12.7
AA-35-P	13.25	337	17.00	432	23.69	602	10.00	254	0.96	25	11.3
AA-35-AM2180	32.67	830	38.00	965	40.25	1022			2.18	54	24.5
AA-36	32.67	830	19.50	495	23.69	602	13.00	330	1.22	46	20.9
AA-36-WM	11.00	279	7.00	178	39.30	998			1.55	52	23.6
AA-36-P	13.25	337	17.00	432	23.69	602	13.00	330	1.37	49	22.2
AA-36-AM2180	35.00	889	42.00	1067	42.75	1035			3.00	102	46.3
AA-135	35.00	889	17.50	445	21.00	533	12.00	305	0.88	29	13.2
AA-135-WM	11.00	279	7.00	178	35.75	908			1.21	35	15.9
AA-135-P	13.25	337	17.00	432	23.69	602	12.00	305	1.03	32	14.5
AA-135-AM2180	32.67	830	38.00	965	40.25	1022			2.32	68	30.8
AA-136	32.67	830	19.50	495	23.69	602	15.00	381	1.31	53	24.0
AA-136-WM	11.00	279	7.00	178	39.30	998			1.64	59	26.8
AA-136-P	13.25	337	17.00	432	23.69	602	13.00	330	1.46	56	25.4
AA-136-AM2180	35.00	889	42.00	1067	42.75	1035			3.18	116	52.6

