

- Pedestrian Areas**
- Walkways**
- Building Entrances**
- Parking Lots**
- Shopping Malls**
- Landscape Areas**



**AA-35/AA-36**



**AA-135/AA-136**

### Specifications



**Certifications** ETL and CETL listed for wet location. Meets IP65 standard.

**Housing** The housing shall be constructed of heavy duty cast aluminum with a minimum 3/16" wall thickness.

**Shade** The shade shall be constructed of heavy duty cast aluminum with a minimum 3/16" wall thickness.

**Mounting Detail** The fixture arm shall internally slip fit a 3" or 4" O.D. pole. Consult Factory for other pole sizes.

The Arm Mount (AM) brackets shall externally slip fit a 3" or 4" O.D. pole. Consult Factory for other pole sizes.

The pendant mounted option (P) is supported by an aluminum pipe 1" O.D. (specify length) with a hang straight bracket (max. 25° slope) attached with two 3/8" bolts on a 5-3/4" bolt circle and a canopy for mounting over a recessed 4" square junction box.

**Ballast** The ballast shall be readily accessible, removable and insulated. The fixture is to be pre-wired and electronically tested before shipment.


**Lens** The lens shall be opal acrylic for wide angle light distribution.

**Lamp Holder** The standard lamp holder shall be 4KV pulse rated medium base, for HID and Incandescent lamp sources.

**Hardware** All exposed hardware shall be stainless steel.

**Finish** BK-BZ-WH-GR-GY-NA are thermoset polyester powder coat. Custom color available upon request.

<b>PROJECT</b>
<b>FIXTURE TYPE</b>
<b>CATALOG#</b>

 Some luminaires use fluorescent or high intensity discharge (HID) lamps that contain small amounts of mercury. Such lamps are labeled "Contains Mercury" and/or with the symbol "Hg." Lamps that contain mercury must be disposed of in accordance with local requirements. Information regarding lamp recycling and disposal can be found at [www.lamprecycle.org](http://www.lamprecycle.org)

# AA-135/AA-136 AA-35/AA-36

## Product Order Guide

Series	Max Watts	Lamp Type	Voltage <sup>1</sup>	Finish <sup>2</sup>	Options
AA-35/AA-135	26 CT	CFT	120	BK Black	WM Wall Mount
	32 CFT	CFT	208	BZ Bronze	P <sup>3</sup> Specify Pendant Length
	42 CFT	CFT	240	WH White	AM2180 <sup>4</sup> Pole adaptor 2 @ 180°
	50 MH	E17	277	GR Green	AM3120 <sup>4</sup> Pole adaptor 3 @ 120°
	70 MH	E17		NA Natural Aluminum	AM490 <sup>4</sup> Pole adaptor 4 @ 90°
	100 MH	E17		GY Gray	S3 3" Internal Slip Fitter
	50 HPS	E17		CC Custom Color	S4 4" Internal Slip Fitter
	70 HPS	E17			
AA-36/AA-136	150 HPS 150 MH	E17 E17			

<sup>1</sup> Consult factory for other voltages.

<sup>2</sup> Thermoset polyester powder coat standard. Custom colors available on request.

<sup>3</sup> Specify pendant length in inches or mm.

<sup>4</sup> Specify pole size.

Note: E17 Lamps 150W and below are medium base  
CFT=triple biac

**Example: AA-35-100MH-E17-277-BK-WM**

## Luminaire Dimensions

Luminaire	A		B		C		D		EPA	Weight	
	Inch	mm	Inch	mm	Inch	mm	Inch	mm		lbs.	kg
AA-35	35.00	889	17.50	445	21.00	533	10.00	254	0.81	22	10.0
AA-35-WM	11.00	279	7.00	178	35.75	908			1.14	28	12.7
AA-35-P	13.25	337	17.00	432	23.69	602	10.00	254	0.96	25	11.3
AA-35-AM2180	32.67	830	38.00	965	40.25	1022			2.18	54	24.5
AA-36	32.67	830	19.50	495	23.69	602	13.00	330	1.22	46	20.9
AA-36-WM	11.00	279	7.00	178	39.30	998			1.55	52	23.6
AA-36-P	13.25	337	17.00	432	23.69	602	13.00	330	1.37	49	22.2
AA-36-AM2180	35.00	889	42.00	1067	42.75	1035			3.00	102	46.3
AA-135	35.00	889	17.50	445	21.00	533	12.00	305	0.88	29	13.2
AA-135-WM	11.00	279	7.00	178	35.75	908			1.21	35	15.9
AA-135-P	13.25	337	17.00	432	23.69	602	12.00	305	1.03	32	14.5
AA-135-AM2180	32.67	830	38.00	965	40.25	1022			2.32	68	30.8
AA-136	32.67	830	19.50	495	23.69	602	15.00	381	1.31	53	24.0
AA-136-WM	11.00	279	7.00	178	39.30	998			1.64	59	26.8
AA-136-P	13.25	337	17.00	432	23.69	602	13.00	330	1.46	56	25.4
AA-136-AM2180	35.00	889	42.00	1067	42.75	1035			3.18	116	52.6

