

- Building Entrances**
- Doorways**
- Walkways**
- Accent and**
- General Lighting**



BL-125



BL-126



BL-127-UD Up/Downlight

## Specifications



**Certifications** The fixture shall be ETL and CETL listed for wet location and have a protection rating of IP65, dust-tight and jet-water proof.

**Housing** The housing shall be constructed of extruded aluminum and cast aluminum door frames.

**Ballast** The ballast shall be readily accessible, removable and insulated. The fixture is to be pre-wired and electronically tested before shipment.

**Lens** The lens shall be clear tempered glass.

**Reflector** The reflector shall be textured aluminum and silver anodized.

**Mounting Detail** The fixture shall be pendant, ceiling or wall mounted.

Pendant mounting detail — supported by a 5/8" diameter aluminum pipe (specify length) with hang straight bracket (maximum 30° slope) and canopy for mounting to 4" octagon box. Mounting hardware by others.

Surface mounting detail — attached to ceiling through two 1/4" holes at 180° with 6-5/16" bolt circle. Mounting hardware by others.

Wall mounting detail — wall mounting plate is attached to wall through four 1/2" holes at 90° on a 6"h x 4"w bolt pattern to mount over 4" octagon box. Mounting hardware by others.

**Hardware** All exposed hardware shall be stainless steel.

**Finish** BK-BZ-WH-GR-GY-NA thermoset polyester powder coat which is electrostatically applied and bonded by heat fusion thermosetting. CC available upon request.

BL

PROJECT
FIXTURE TYPE
CATALOG#

# BL-125/126/127

 Some luminaires use fluorescent or high intensity discharge (HID) lamps that contain small amounts of mercury. Such lamps are labeled "Contains Mercury" and/or with the symbol "Hg." Lamps that contain mercury must be disposed of in accordance with local requirements. Information regarding lamp recycling and disposal can be found at [www.lamprecycle.org](http://www.lamprecycle.org)

## Product Order Guide


Series	Max Watts	Lamp Type	Voltage <sup>1</sup>	Finish <sup>1</sup>	Options
BL-125/126	26 CFT	CFT <sup>2</sup>	120	BK Black	P <sup>3</sup> Specify Pendant Length
	32 CFT	CFT <sup>2</sup>	208	BZ Bronze	SPT Nema 1 (E17 & T6)
	42 CFT	CFT <sup>2</sup>	240	WH White	FLD Nema 3 (E17 & T6)
	39 MH	T6	277	GR Green	RB Remote Ballast
	70 MH	T6		NA Natural Aluminum	SPT Spot T6/E17
	70 MH	PAR38		GY Gray	FLD Flood T6/E17
	50 MH	E17		CC Custom Color	MFLD Medium Flood T6/E17
	70 MH	E17			
	50 HPS	E17			
	70 HPS	E17			
BL-127	26 CFT	CFT <sup>2</sup>			D Downlight
	32 CFT	CFT <sup>2</sup>			UD Up/Downlight
	42CFT	CFT <sup>2</sup>			U Uplight
	70 MH	PAR38			SPT Nema 1 (E17 & T6)
	50 MH	E17			FLD Nema 3 (E17 & T6)
	70 MH	E17			RB Remote Ballast
	39 MH	T6			SPT Spot T6/E17
	70 MH	T6			FLD Flood T6/E17
	50 HPS	E17			MFLD Medium Flood T6/E17
	70 HPS	E17			
	Titan25WW	CUS3 <sup>4</sup>	120-277	Beam 25° Warm White (3050K)	
	Titan25CW	CUS3 <sup>4</sup>	120-277	Beam 25° Cool (Daylight) White (4700K)	

1 Consult factory for other colors and voltages  
3 BL-125 only


2 CFT = triple biax  
4 The CUS3 is a 25W Titan LED from Lamina and work in BL-125, BL-126 and BL-127

## Example: BL-125-13CF-120-BK-P30"

### Photometric Data



BL-125-26CFT-FLD  
1610 Lumens  
8.0 ft Mounting Height  
value in initial footcandles



BL-126-70MH-E17-FLD  
6200 Lumens  
8.0 ft Mounting Height  
value in initial footcandles

### Luminaire Dimensions

Luminaire	A		B		C		D		E		Weight	
	Inch	mm	Inch	mm	Inch	mm	Inch	mm	Inch	mm	lbs.	kg
BL-125	8.00	203	12.40	315	71.01	1805					6.2	2.8
BL-126	8.00	203	12.40	315							10.6	4.8
BL-127-D	8.00	203	12.01	305					11.42	290	11.5	5.2
BL-127-UD	8.00	203					20.50	508	11.50	292	20.0	9.0

